

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

- Trade name: **Akepox 1009 Component B**
- Article number: 11682, 11683, 11684, 11685, 11690, 13682, 13683, 13684, 13690, 11716, 13716
- UFI: VJU1-9071-H00W-1CWC

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

### Application of the substance / the mixture

Reaction resin

### 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg
- Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

### Further information obtainable from:

Laboratory

### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.  
+44 (171) 635 91 91  
National Poison Inform. Centre  
Medical Toxicology Unit  
Avalonley Road  
London SE14 5ER

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

- Acute Tox. 4 H302 Harmful if swallowed.
- Acute Tox. 4 H312 Harmful in contact with skin.
- Skin Corr. 1B H314 Causes severe skin burns and eye damage.
- Eye Dam. 1 H318 Causes serious eye damage.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

### Signal word

Danger

### Hazard-determining components of labelling:

2-piperazin-1-ylethylamine  
1,3-Cyclohexanedimethanamine  
m-phenylenebis(methylamine)  
phenole, styrenated

### Hazard statements

H302+H312 Harmful if swallowed or in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 1)

· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P260	Do not breathe vapours.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 140-31-8 EINECS: 205-411-0 Index number: 612-105-00-4 Reg.nr.: 01-2119471486-30-0000	2-piperazin-1-ylethylamine Acute Tox. 3, H311 Repr. 2, H361; STOT RE 1, H372 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-xxxx	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	25-50%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	12.5-25%
CAS: 69-72-7 EINECS: 200-712-3 Index number: 607-732-00-5 Reg.nr.: 01-2119486984-17	salicylic acid Repr. 2, H361d Eye Dam. 1, H318 Acute Tox. 4, H302	1-5%
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119979575-18	phenole, styrenated Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	1-5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures**

- General information: Take affected persons out into the fresh air.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 2)

- Position and transport stably in side position.  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After inhalation:
  - After skin contact:
  - After eye contact:
  - After swallowing:
  - Information for doctor:
- If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.  
Immediately rinse with water.  
Rinse opened eye for several minutes under running water. Then consult a doctor.  
Call for a doctor immediately.  
Drink plenty of water and provide fresh air. Call for a doctor immediately.  
The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight  $\leq 300$ . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.  
Bisphenol-A based resins: Inhalation, swallowing or dermal incorporation may cause health damage. Irritates respiratory tract, digestion system, eyes and skin: e.g., cough, dyspnea, lacrimation, burning. May cause health interferences such as dermal changes, renal, hepatic damage, and blood count changes. May provoke skin allergies. Sensitized users can react towards very low concentrations of Bisphenol-A-Epichlorhydrine and should avoid any further contact with this chemical.  
Nonylphenol based exposition: causes corrosive burns, damages respiratory tract, eyes, skin and digestive system up to complete tissue destruction. Temporary dysfunctions such as dizziness, headache, nausea and diarrhea may occur. Can cause health disturbances like dermal bleaching, renal and hepatic damage.
- **4.2 Most important symptoms and effects, both acute and delayed**
  - Hazards
  - **4.3 Indication of any immediate medical attention and special treatment needed**
- Allergic reactions  
Headache  
Dizziness  
Dizziness  
Breathing difficulty  
Profuse sweating  
Nausea
- Danger of impaired breathing.  
Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.
- If swallowed, gastric irrigation with added, activated carbon.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
  - Suitable extinguishing agents:
  - **5.2 Special hazards arising from the substance or mixture**
- CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Formation of toxic gases is possible during heating or in case of fire.  
In case of fire, the following can be released:

(Contd. on page 4)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 3)

- **5.3 Advice for firefighters**
- Protective equipment: Carbon monoxide (CO)  
Nitrogen oxides (NOx)  
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- Additional information Wear fully protective suit.  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Use only in well ventilated areas.  
Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.  
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Store receptacle in a well ventilated area.  
Keep container tightly sealed.
- Storage class: 8 A
- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 5)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

· Additional information about design of technical facilities:

No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs**140-31-8 2-piperazin-1-ylethylamine**

Dermal	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	10.6 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	10.6 mg/m <sup>3</sup> Air (ARB)

**2579-20-6 1,3-Cyclohexanedimethanamine**

Inhalative	DNEL (Langzeit-wiederholt)	0.00947 mg/m <sup>3</sup> Air (ARB)
------------	----------------------------	-------------------------------------

**1477-55-0 m-phenylenebis(methylamine)**

Dermal	DNEL (Langzeit-wiederholt)	0.33 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	1.2 mg/m <sup>3</sup> Air (ARB)

**69-72-7 salicylic acid**

Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (ARB)
		1 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	16 mg/m <sup>3</sup> Air (ARB)
		0.2-4 mg/m <sup>3</sup> Air (BEV)

· PNECs**140-31-8 2-piperazin-1-ylethylamine**

PNEC (wässrig)	250 mg/l (KA)
	0.0058 mg/l (MW)
	0.058 mg/l (SW)
	0.58 mg/l (WAS)
PNEC (fest)	21.51 mg/kg Trockengew (MWS)
	215 mg/kg Trockengew (SWS)

**2579-20-6 1,3-Cyclohexanedimethanamine**

PNEC (wässrig)	10 mg/l (KA)
	0.003 mg/l (MW)
	0.033 mg/l (SW)

**1477-55-0 m-phenylenebis(methylamine)**

PNEC (wässrig)	10 mg/l (KA)
	0.0094 mg/l (MW)
	0.094 mg/l (SW)
	0.152 mg/l (WAS)
PNEC (fest)	0.045 mg/kg Trockengew (BO)
	0.043 mg/kg Trockengew (MWS)
	0.43 mg/kg Trockengew (SWS)

**69-72-7 salicylic acid**

PNEC (wässrig)	162 mg/l (KA)
----------------	---------------

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 5)

PNEC (fest)	0.02 mg/l (MW)
	0.2 mg/l (SW)
	0.166 mg/kg Trockengew (BO)
	0.142 mg/kg Trockengew (MWS)
	1.42 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:  
 · General protective and hygienic measures:

Use skin protection cream for skin protection.  
 Clean skin thoroughly immediately after handling the product.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.  
 Short term filter device:  
 Filter A/P2

· Protection of hands:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
 Preventive skin protection by use of skin-protecting agents is recommended.  
 After use of gloves apply skin-cleaning agents and skin cosmetics.  
 Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:  
 STOKO EMULSION (<http://www.stoko.com>)  
 Skin protection recommendation for skin cleaning after product handling:  
 Kresto Classic (<http://debstoko.com>)  
 Skin protection agent recommendation for skin aftercare:  
 STOKO VITAN (<http://www.stoko.com>)  
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.  
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR  
 Nitrile rubber, NBR  
 Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 6)

- material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level  $\leq$  6, 480 min  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - For the permanent contact gloves made of the following materials are suitable:  
Butyl rubber, BR  
Butoject (KCL, Art\_No. 897, 898)  
Nitrile rubber, NBR  
Camatril (KCL, Art\_No. 730, 731, 732, 733)  
Dermatril (Art\_No. 740, 741, 742)  
Chloroprene rubber, CR  
Camapren (KCL, Art\_No. 720, 722, 726)
  - As protection from splashes gloves made of the following materials are suitable:  
Nitrile rubber, NBR  
Dermatril (KCL, Art\_No. 740, 741, 742)  
Camatril (KCL, 730, 731, 732, 733)  
Chloroprene rubber, CR  
Camapren (KCL, Art\_No. 720, 722, 726)
  - Not suitable are gloves made of the following materials:  
Leather gloves  
Strong material gloves
  - Eye protection:  
 Tightly sealed goggles
  - Body protection:  
Protective work clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**General InformationAppearance:

Form:	Fluid
Colour:	Yellowish
Odour:	Amine-like

· pH-value: Not applicable

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>200 °C

· Flash point: >100 °C

· Ignition temperature: 315 °C

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower:	2.1 Vol %
Upper:	10.5 Vol %

· Vapour pressure at 20 °C: 0.1 hPa

· Density at 20 °C: 1.03 g/cm<sup>3</sup>

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 7)

· <u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
· <u>Viscosity:</u>	
<u>Dynamic at 20 °C:</u>	120 mPas
<u>Kinematic:</u>	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

**SECTION 10: Stability and reactivity**

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used and stored according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	Strong exothermic reaction with acids.
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	Corrosive gases/vapours

**SECTION 11: Toxicological information**

· <b>11.1 Information on toxicological effects</b>	
· <u>Acute toxicity</u>	Harmful if swallowed or in contact with skin.

· LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Oral	LD50	1,081-<1,185 mg/kg (rat)
Dermal	LD50	1,510 mg/kg
Inhalative	LC50/4 h	13.3 mg/l (rat)

**140-31-8 2-piperazin-1-ylethylamine**

Oral	LD50	2,097 mg/kg (rabbit)
		1,470-2,140 mg/kg (rat)
Dermal	LD50	866 mg/kg (rabbit)
		866-1,260 mg/kg (rat)

**2579-20-6 1,3-Cyclohexanedimethanamine**

Oral	LD50	700 mg/kg (rat)
	LD0	>300 mg/kg (rat)
	LD100	2,000 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)

**1477-55-0 m-phenylenebis(methylamine)**

Oral	LD50	<2,000 mg/kg (rat)
	NOEL	150 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	2.4 mg/l (rat)
	LC50/1h	3.89 mg/l (rat)

**69-72-7 salicylic acid**

Oral	LD50	891 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat) (OECD 416)

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 8)

Dermal	LD50	>2,000 mg/kg (rabbit)
	LC50/48h	90 mg/l (Leuciscus idus)
<b>61788-44-1 phenole, styrenated</b>		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>5,010 mg/kg (rabbit)
		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>4.9 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**· **12.1 Toxicity**· Aquatic toxicity:**140-31-8 2-piperazin-1-ylethylamine**

EC50	511 mg/l (bacteria)
EC50/48h	58 mg/l (daphnia magna)
	494 mg/l (Selenastrum capricornutum)
EC20/0.5h	>1,000 mg/l (BES)
EC50/72h	>1,000 mg/l (pseudomonas putida)
	494 mg/l (Selenastrum capricornutum)
LC50/96h	2,190 mg/l (piscis)
	368 mg/l (Leuciscus idus)
	>100 mg/l (Oncorhynchus mykiss)
	>1,800 mg/l (poecilia reticulata)

**2579-20-6 1,3-Cyclohexanedimethanamine**

EC50	>1,000 mg/l (BES)
	90 mg/l (pseudomonas putida)
EC50/48h	65.4 mg/l (daphnia magna)
ErC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)
LC100/96h	180 mg/l (Leuciscus idus)
NOELR/72h	14.4 mg/l (Pseudokirchneriella subcapitata)
EC50/72h	58.4 mg/l (selenastrum capricornutum)
LC50/96h	130 mg/l (Leuciscus idus)
EBC50	58.4 mg/l (Pseudokirchneriella subcapitata)

**1477-55-0 m-phenylenebis(methylamine)**

EC50/48h	15.2 mg/l (daphnia magna)
EC50/30min	>1,000 mg/l (BES)
NOEC/21d	4.7 mg/l (daphnia magna)

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 9)

EC50/72h	12 mg/l (Scenedesmus subspicatus) 32.1 mg/l (selenastrum capricornutum)
LC50/96h	>100 mg/l (Oncorhynchus mykiss) 87.6 mg/l (Oryzias latipes) >100 mg/l (Zebraabärbling)

**69-72-7 salicylic acid**

EC50	380 mg/l (BES) (OECD 209)
LC50/24h	105-230 mg/l (daphnia magna)
EC50/48h	870 mg/l (daphnia magna) (OECD 202)
EC50/16h	380 mg/l (bacteria)
NOEC/21d	10 mg/l (daphnia magna) (OECD 202 II)
EC50/72h	>100 mg/l (green alge) (OECD 201)
LC50/96h	1,370 mg/l (piscis) (OECD 203) 1,380 mg/l (pimephales promelas)

**61788-44-1 phenole, styrenated**

EC50	362 mg/l (BES) 3.8 mg/l (piscis)
EL50/48h	4.6 mg/l (daphnia magna)
EL50/72h	20.42 mg/l (CHV) 3.14 mg/l (Scenedesmus subspicatus)
LL50/96h	14.8 mg/l (piscis)
NOEC/21d	0.2 mg/l (daphnia magna)
LC50/96h	>1-10 mg/l (Brachydanio rerio)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- Ecotoxicological effects:

- Remark:

Toxic for fish

- Additional ecological information:

- General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

- **12.5 Results of PBT and vPvB assessment**

- PBT:

Not applicable.

- vPvB:

Not applicable.

- **12.6 Other adverse effects**

No further relevant information available.

\* **SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:

- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

- Recommended cleansing agents:

Alcohol  
acetone

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021



Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 10)

**SECTION 14: Transport information**

· <b>14.1 UN-Number</b> · <u>ADR, IMDG, IATA</u>	UN2735
· <b>14.2 UN proper shipping name</b> · <u>ADR</u>  · <u>IMDG, IATA</u>	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-, triethylenetetraamine fraction, N-AMINOETHYLPIPERAZINE) AMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-, triethylenetetraamine fraction, N-AMINOETHYLPIPERAZINE)
· <b>14.3 Transport hazard class(es)</b> · <u>ADR</u>    · <u>Class</u> · <u>Label</u>	8 (C7) Corrosive substances. 8
· <u>IMDG, IATA</u>    · <u>Class</u> · <u>Label</u>	8 Corrosive substances. 8
· <b>14.4 Packing group</b> · <u>ADR, IMDG, IATA</u>	II
· <b>14.5 Environmental hazards:</b> · <u>Marine pollutant:</u>	Product contains environmentally hazardous substances: Yes
· <b>14.6 Special precautions for user</b> · <u>Hazard identification number (Kemler code):</u> · <u>EMS Number:</u> · <u>Segregation groups</u> · <u>Stowage Category</u> · <u>Segregation Code</u>	Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" SGG1-acids
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <u>Transport/Additional information:</u>  · <u>ADR</u> · <u>Excepted quantities (EQ)</u>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <u>IMDG</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <u>UN "Model Regulation":</u>	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (AMINES, POLYETHYLENEPOLY-, TRIETHYLENETETRAAMINE FRACTION, N-

(Contd. on page 12)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 11)

AMINOETHYLPIPERAZINE), 8, II

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· VOC EU

0.0 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H361 Suspected of damaging fertility or the unborn child.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use

refer to Technical Data Sheet (TDS)

· Department issuing SDS:

Laboratory

· Contact:

Dieter Zimmermann

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Acute Tox. 4: Acute toxicity – Category 4  
Acute Tox. 3: Acute toxicity – Category 3

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 7

Revision: 16.03.2021

**Trade name: Akepox 1009 Component B**

(Contd. of page 12)

Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Repr. 2: Reproductive toxicity – Category 2  
Repr. 2: Reproductive toxicity – Category 2  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB