

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Akepox 2000 Component B**

Article number: 10617, 10618, 10619,0

UFI: X783-W0J3-E00T-Q4H6

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H332	Harmful if inhaled.
Skin Corr. 1B	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Muta. 2	H341	Suspected of causing genetic defects.
Repr. 2	H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07 GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine
Benzyl alcohol
4-nonylphenol, branched phenol
formaldehyde polymer with 1,3-benzenedimethanamine and phenol
m-phenylenebis(methylamine)
N-(3-(trimethoxysilyl)propyl)ethylenediamine
3-aminomethyl-3,5,5-trimethylcyclohexylamine
H332 Harmful if inhaled.
H314 Causes severe skin burns and eye damage.

Hazard statements

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 1)

<u>Precautionary statements</u>	<p>H317 May cause an allergic skin reaction.</p> <p>H341 Suspected of causing genetic defects.</p> <p>H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P103 Read carefully and follow all instructions.</p> <p>P260 Do not breathe vapours.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/doctor.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
2.3 Other hazards	
Results of PBT and vPvB assessment	
PBT:	Not applicable.

vPvB:

1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**Description: Mixture of substances listed below with nonhazardous additions.Dangerous components:

CAS: 38294-64-3 NLP: 500-101-4 Reg.nr.: 01-2119965165-33	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
CAS: 1950616-36-0 EC number: 701-207-5 Reg.nr.: 01-2119966906-20	formaldehyde polymer with 1,3-benzenedimethanamine and phenol Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	12.5-25%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	12.5-25%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<12.5%
CAS: 84852-15-3 EINECS: 284-325-5 Index number: 601-053-00-8 Reg.nr.: 01-2119510715-45-xxxx	4-nonylphenol, branched Repr. 2, H361fd Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302	1-5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 2)

CAS: 69-72-7 EINECS: 200-712-3 Index number: 607-732-00-5 Reg.nr.: 01-2119486984-17	salicylic acid Repr. 2, H361d Eye Dam. 1, H318 Acute Tox. 4, H302	1-5%
CAS: 108-95-2 EINECS: 203-632-7 Index number: 604-001-00-2 Reg.nr.: 01-2119471329-32	phenol Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Muta. 2, H341; STOT RE 2, H373 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Chronic 2, H411	1-5%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39	N-(3-(trimethoxysilyl)propyl)ethylenediamine STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H332; Skin Sens. 1, H317 vPvB	1-5%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-0000	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 Aquatic Chronic 3, H412	1-5%

· **SVHC**

84852-15-3 4-nonylphenol, branched

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**· **4.1 Description of first aid measures**

- **General information:** Take affected persons out into the fresh air.
Position and transport stably in side position.
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **Information for doctor:** The symptoms of phenol based poisonings appearances are white coloured mouth scabs, shock condition, insensibility, bradycardia and renal dysfunction and damage of renal tissue. Appropriate therapy measures: Administration of an adequate volume of liquid, gastrolavage in application of carbo medicinalis, sodium sulphate with plenty of water, infusion of glucose solution (5%); measures against state of shock, hemodialysis.
Nonylphenol based exposition: causes corrosive burns, damages respiratory tract, eyes, skin and digestive system up to complete tissue destruction. Temporary dysfunctions such as dizziness, headache, nausea and diarrhea may occur. Can cause health disturbances like dermal bleaching, renal and hepatic damage.
Amines: Inhalation, swallowing or dermal contact may cause health damages. Cause burns, harm respiratory tract, eyes, skin, and digestion system in worst case up to complete destruction. Intermediate interferences such as headache, nausea, cough, dyspnea may occur. May cause allergies. Sensitized users may react towards very low amine concentrations and should avoid any further contact with this group of chemicals.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 3)

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty
Headache
Dizziness
Coughing
Danger of impaired breathing.

· Hazards

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NOx)
Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear fully protective suit.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Mount respiratory protective device.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 4)

Store in cool, dry place in tightly closed receptacles.
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from oxidising agents.
Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.
Keep container tightly sealed.

· Storage class:

8 A

· **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· Additional information about design of technical facilities:

No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

108-95-2 phenol

WEL	Short-term value: 16 mg/m ³ , 4 ppm
	Long-term value: 7.8 mg/m ³ , 2 ppm
	Sk

· DNELs

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

Oral	DNEL (Kurzzeit-akut)	3.33 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	3.33 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.00385-2.8 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	0.000167-0.008 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	2-6 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	0.02 mg/m ³ Air (ARB)

100-51-6 Benzyl alcohol

Oral	DNEL (Kurzzeit-akut)	25 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	47 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	28.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	9.5 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	5.7 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	450 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	40.55 mg/m ³ Air (BEV)
		90 mg/m ³ Air (ARB)
		8.11 mg/m ³ Air (BEV)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 5)

1477-55-0 m-phenylenebis(methylamine)

Dermal	DNEL (Langzeit-wiederholt)	0.33 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	1.2 mg/m ³ Air (ARB)

84852-15-3 4-nonylphenol, branched

Dermal	DNEL (Langzeit-wiederholt)	7.5 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	0.5 mg/m ³ Air (ARB)

69-72-7 salicylic acid

Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (ARB)
		1 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	16 mg/m ³ Air (ARB)
		0.2-4 mg/m ³ Air (BEV)

108-95-2 phenol

Oral	DNEL (Langzeit-wiederholt)	0.4 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	0.4 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	8 mg/m ³ Air (ARB)
		1.32 mg/m ³ Air (BEV)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral	DNEL (Langzeit-wiederholt)	2.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	5 mg/kg bw/day (ARB)
		17 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	5 mg/kg bw/day (ARB)
		2.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	35.3 mg/m ³ Air (ARB)
		8.7 mg/m ³ Air (BEV)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	DNEL (Langzeit-wiederholt)	0.526 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	20.1 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	0.073 mg/m ³ Air (ARB)

PNECs**1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol**

PNEC (wässrig)	30 mg/l (KA)
	0.002 mg/l (MW)
	0.02 mg/l (SW)
PNEC (fest)	0.0236 mg/kg Trockengew (BO)
	0.01 mg/kg Trockengew (MWS)
	0.1001 mg/kg Trockengew (SWS)

100-51-6 Benzyl alcohol

PNEC (wässrig)	39 mg/l (KA)
	0.1 mg/l (MW)
	1 mg/l (SW)
	2.3 mg/l (WAS)
PNEC (fest)	0.456 mg/kg Trockengew (BO)
	0.527 mg/kg Trockengew (MWS)
	5.27 mg/kg Trockengew (SWS)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 6)

1477-55-0 m-phenylenebis(methylamine)

PNEC (wässrig)	10 mg/l (KA)
	0.0094 mg/l (MW)
	0.094 mg/l (SW)
	0.152 mg/l (WAS)
PNEC (fest)	0.045 mg/kg Trockengew (BO)
	0.043 mg/kg Trockengew (MWS)
	0.43 mg/kg Trockengew (SWS)

84852-15-3 4-nonylphenol, branched

PNEC (wässrig)	0.000527 mg/l (MW)
	0.000614 mg/l (SW)

69-72-7 salicylic acid

PNEC (wässrig)	162 mg/l (KA)
	0.02 mg/l (MW)
	0.2 mg/l (SW)
PNEC (fest)	0.166 mg/kg Trockengew (BO)
	0.142 mg/kg Trockengew (MWS)
	1.42 mg/kg Trockengew (SWS)

108-95-2 phenol

PNEC (wässrig)	2.1 mg/l (KA)
	0.00077 mg/l (MW)
	0.0077 mg/l (SW)
PNEC (fest)	0.136 mg/kg Trockengew (BO)
	0.00915 mg/kg Trockengew (MWS)
	0.0915 mg/kg Trockengew (SWS)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

PNEC (wässrig)	25 mg/l (KA)
	0.0062 mg/l (MW)
	0.062 mg/l (SW)
	0.62 mg/l (WAS)
PNEC (fest)	0.0075 mg/kg Trockengew (BO)
	0.005 mg/kg Trockengew (MWS)
	0.05 mg/kg Trockengew (SWS)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

PNEC (wässrig)	3.18 mg/l (KA)
	0.006 mg/l (MW)
	0.06 mg/l (SW)
	0.23 mg/l (WAS)
PNEC (fest)	1.121 mg/kg Trockengew (BO)
	0.578 mg/kg Trockengew (MWS)
	5.784 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:
 · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 7)

- Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- Respiratory protection:
Short term filter device:
Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:
Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Skin protection recommendation for skin cleaning after product handling:
Kresto Classic (<http://debstoko.com>)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
-  Protective gloves
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
Butyl rubber, BR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
Value for the permeation: Level ≤ 6, 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Dermatril (Art_No. 740, 741, 742)
Camatril (KCL, Art_No. 730, 731, 732, 733)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 8)

- As protection from splashes gloves made of the following materials are suitable:
Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)
- Not suitable are gloves made of the following materials:
Natural rubber, NR
Fluorocarbon rubber (Viton)
- Eye protection:
 Tightly sealed goggles
- Body protection:
Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**General InformationAppearance:

- | | |
|----------------|----------------|
| <u>Form:</u> | Fluid |
| <u>Colour:</u> | Yellow |
| <u>Odour:</u> | Characteristic |

Change in condition

- | | |
|---|---------------|
| <u>Melting point/freezing point:</u> | Undetermined. |
| <u>Initial boiling point and boiling range:</u> | 205 °C |

- | | |
|---------------------|--------|
| <u>Flash point:</u> | 101 °C |
|---------------------|--------|

- | | |
|------------------------------|--------|
| <u>Ignition temperature:</u> | 380 °C |
|------------------------------|--------|

- | | |
|-----------------------------------|----------|
| <u>Decomposition temperature:</u> | > 250 °C |
|-----------------------------------|----------|

- | | |
|-----------------------------------|------------------------------|
| <u>Auto-ignition temperature:</u> | Product is not selfigniting. |
|-----------------------------------|------------------------------|

- | | |
|------------------------------|---|
| <u>Explosive properties:</u> | Product does not present an explosion hazard. |
|------------------------------|---|

Explosion limits:

- | | |
|---------------|-----------|
| <u>Lower:</u> | 1.3 Vol % |
| <u>Upper:</u> | 13 Vol % |

- | | |
|----------------------------------|---------|
| <u>Vapour pressure at 20 °C:</u> | 0.1 hPa |
|----------------------------------|---------|

- | | |
|--------------------------|------------------------|
| <u>Density at 20 °C:</u> | 1.06 g/cm ³ |
|--------------------------|------------------------|

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Viscosity:

- | | |
|--------------------------|-----------------|
| <u>Dynamic at 20 °C:</u> | 5,000 mPas |
| <u>Kinematic:</u> | Not determined. |

Solvent content:

- | | |
|--------------------------|--------|
| <u>Organic solvents:</u> | 17.9 % |
|--------------------------|--------|

- | | |
|------------------------------|--|
| 9.2 Other information | No further relevant information available. |
|------------------------------|--|

SECTION 10: Stability and reactivity

- | | |
|------------------------|--|
| 10.1 Reactivity | No further relevant information available. |
|------------------------|--|

10.2 Chemical stabilityThermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 9)

- **10.3 Possibility of hazardous reactions**
Strong exothermic reaction with acids.
Reacts with strong oxidising agents.
- **10.4 Conditions to avoid**
No further relevant information available.
- **10.5 Incompatible materials:**
No further relevant information available.
- **10.6 Hazardous decomposition products:**
Corrosive gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	2,302 mg/kg
Dermal	LD50	7,664 mg/kg
Inhalative	LC50/4 h	13.6 mg/l

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,020 mg/kg (rat)

100-51-6 Benzyl alcohol

Oral	LD50	1,040 mg/kg (mouse)
		1,040 mg/kg (rabbit)
		1,620 mg/kg (rat)
	NOEL	400 mg/kg (rat)
	NOAEL	200 mg/kg (mouse)
		400 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	11 mg/l (rat)
	LC50/48h	360 mg/l (daphnia magna)
		645 mg/l (goo)

1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	<2,000 mg/kg (rat)
	NOEL	150 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	2.4 mg/l (rat)
	LC50/1h	3.89 mg/l (rat)

84852-15-3 4-nonylphenol, branched

Oral	LD50	1,210 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	3.636 mg/l (mouse)

69-72-7 salicylic acid

Oral	LD50	891 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat) (OECD 416)
Dermal	LD50	>2,000 mg/kg (rabbit)
	LC50/48h	90 mg/l (Leuciscus idus)

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 10)

108-95-2 phenol

Oral	LD50	300 mg/kg (mouse) 317 mg/kg (rat)
Dermal	LD50	630 mg/kg (rat)
Inhalative	LC50/4 h	316 mg/l (rat)
	LC50/8h	0.9 mg/l (rat)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral	LD50	2,995 mg/kg (rat)
	NOEL	≥500 mg/kg (rat) (OECD 422)
	NOAEL	≥500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	1.49 mg/l (rat)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1,030 mg/kg (rat)
	NOAEL-Werte	>250 mg/kg (rat)
Dermal	LD50	1,840 mg/kg (rabbit) >2,000 mg/kg (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Suspected of causing genetic defects.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging fertility. Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**Aquatic toxicity:**38294-64-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EC50	>1,000 mg/l (BES)
EL50/48h	11.1 mg/l (daphnia magna)
EL50/72h	79.4 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	70.7 mg/l (Oncorhynchus mykiss)

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

EC50	491.3 mg/l (BES)
EC50/48h	29.8 mg/l (daphnia magna)
EC50/72h	20.4 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	25.9 mg/l (Oncorhynchus mykiss)

100-51-6 Benzyl alcohol

EC50/24h	55-400 mg/l (daphnia magna)
EC50/96h	640 mg/l (Scenedesmus pluvialis)
EC50	2,100 mg/l (BES) (OECD 209)

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 11)

EC10/16h	79 mg/l (Scenedesmus quadricauda) 658 mg/l (pseudomonas putida)
EC50/48h	230 mg/l (daphnia magna) (OECD 202)
EC0	640 mg/l (Scenedesmus quadricauda)
EC50/16h	658 mg/l (pseudomonas putida)
EC50/30min	71.4 mg/l (Photobac. phosphoreum) 400 mg/l (pseudomonas putida)
IC5/96h	640 mg/l (Scenedesmus quadricauda)
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)
NOEC/21d	51 mg/l (daphnia magna) (OECD211)
EC50/72h	770 mg/l (green alge) (OECD 201) 770 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	645 mg/l (goo) 10 mg/l (lepomis macrochirus) 460 mg/l (Pimephales promelas)

1477-55-0 m-phenylenebis(methylamine)

EC50/48h	15.2 mg/l (daphnia magna)
EC50/30min	>1,000 mg/l (BES)
NOEC/21d	4.7 mg/l (daphnia magna)
EC50/72h	12 mg/l (Scenedesmus subspicatus) 32.1 mg/l (selenastrum capricornutum)
LC50/96h	>100 mg/l (Oncorhynchus mykiss) 87.6 mg/l (Oryzias latipes) >100 mg/l (Zebrabärbling)

84852-15-3 4-nonylphenol, branched

EC50/96h	0.41 mg/l (green alge)
EC50/48h	0.085 mg/l (daphnia magna)
NOEC/21d	0.024 mg/l (daphnia magna)
EC50/72h	0.33 mg/l (Scenedesmus subspicatus)
LC50/96h	0.128 mg/l (Pimephales promelas)

69-72-7 salicylic acid

EC50	380 mg/l (BES) (OECD 209)
LC50/24h	105-230 mg/l (daphnia magna)
EC50/48h	870 mg/l (daphnia magna) (OECD 202)
EC50/16h	380 mg/l (bacteria)
NOEC/21d	10 mg/l (daphnia magna) (OECD 202 II)
EC50/72h	>100 mg/l (green alge) (OECD 201)
LC50/96h	1,370 mg/l (piscis) (OECD 203) 1,380 mg/l (pimephales promelas)

108-95-2 phenol

EC50/24h	21 mg/l (BO)
EC50/96h	61.1 mg/l (green alge)
EC50/48h	3.1 mg/l (daphnia magna)
LC50/96h	8.9 mg/l (Oncorhynchus mykiss)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

EC50	435 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung)
------	---

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 12)

IC50/72h	8.8 mg/l (green alge) (OECD 201)
EC50/48h	81 mg/l (daphnia magna)
EC50/16h	67 mg/l (pseudomonas putida)
NOEC	3.1 mg/kg (green alge) (OECD 201)
	≥1,000 mg/kg (Eisenia fetida (Regenwürmer)) (OECD 207)
NOEC/21d	>1 mg/l (daphnia magna)
EC50/48h	87.4 mg/l (daphnia magna)
EC50/72h	5 mg/l (green alge)
	126 mg/l (Scenedesmus subspicatus)
LC50/96h	344 mg/l (Brachydanio rerio)
	597 mg/l (Danio rerio.)
	168 mg/l (pimephales promelas)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC50/24h	44 mg/l (daphnia magna)
LC 0/96h	70 mg/l (piscis)
EC10/18h	1,120 mg/l (pseudomonas putida)
EC50/48h	23 mg/l (daphnia magna) (OECD TG 202)
ErC50/72h	>50 mg/l (Scenedesmus subspicatus) (EG 88/302)
NOEC/21d	3 mg/l (daphnia magna)
EC10	11.2 mg/l (Desmodesmus subspicatus)
EC50/72h	37 mg/l (green alge) (EG 88/302)
	37 mg/l (Scenedesmus subspicatus)
LC50/96h	110 mg/l (Brachydanio rerio) (EG 84/449)
	110 mg/l (Leuciscus idus) (EG 84/449)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· Ecotoxicological effects:

· Remark:

Harmful to fish

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· PBT:

Not applicable.

· vPvB:

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

· **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents:

Alcohol

(Contd. on page 14)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9



Revision: 22.03.2021

Trade name: Akepox 2000 Component B

acetone

(Contd. of page 13)

SECTION 14: Transport information

· 14.1 UN-Number · <u>ADR, IMDG, IATA</u>	UN2735
· 14.2 UN proper shipping name · <u>ADR</u> · <u>IMDG, IATA</u>	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, formaldehyde polymer with 1,3-benzenedimethanamine and phenol), ENVIRONMENTALLY HAZARDOUS POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, formaldehyde polymer with 1,3-benzenedimethanamine and phenol)
· 14.3 Transport hazard class(es) · <u>ADR</u>  · <u>Class</u> · <u>Label</u>	8 (C7) Corrosive substances. 8
· <u>IMDG, IATA</u>  · <u>Class</u> · <u>Label</u>	8 Corrosive substances. 8
· 14.4 Packing group · <u>ADR, IMDG, IATA</u>	III
· 14.5 Environmental hazards: · <u>Marine pollutant:</u> · <u>Special marking (ADR):</u>	Product contains environmentally hazardous substances: No Symbol (fish and tree)
· 14.6 Special precautions for user · <u>Hazard identification number (Kemler code):</u> · <u>EMS Number:</u> · <u>Segregation groups</u> · <u>Stowage Category</u> · <u>Segregation Code</u>	Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" SGG1-acids
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.

(Contd. on page 15)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 14)

· Transport/Additional information:· ADR· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IMDG· Limited quantities (LQ)· Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH 3-AMINO METHYL - 3 , 5 , 5 - TRIMETHYLCYCLOHEXYLAMINE, FORMALDEHYDE POLYMER WITH 1,3-BENZENEDIMETHANAMINE AND PHENOL), 8, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

84852-15-3 4-nonylphenol, branched

· VOC EU

190.3 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.

(Contd. on page 16)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 9

Revision: 22.03.2021

Trade name: Akepox 2000 Component B

(Contd. of page 15)

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H341 Suspected of causing genetic defects.
 H361d Suspected of damaging the unborn child.
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

refer to Technical Data Sheet (TDS)

· Recommended restriction of use· Department issuing SDS:· Contact:· Abbreviations and acronyms:

Laboratory

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Muta. 2: Germ cell mutagenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC