

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Solid Wax**
- Article number: 11900, 11905, 11907, 11908
- UFI: M4E2-10QE-A00C-NCCK

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Maintenance product

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Carc. 2 H351 Suspected of causing cancer.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS08 GHS09

Signal word

Warning

Hazard-determining components of labelling:

Hazard statements

tetrachloroethylene
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 1)

- | | | |
|---|---|--|
| <ul style="list-style-type: none"> · <u>Precautionary statements</u> | P101
P102
P103
P261
P273
P280

P302+P352
P305+P351+P338

P312
P333+P313
P403+P233
P405
P501 | If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read carefully and follow all instructions.
Avoid breathing vapours.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
IF ON SKIN: Wash with plenty of water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.
If skin irritation or rash occurs: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations. |
|---|---|--|
- **2.3 Other hazards**
 - Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 127-18-4 EINECS: 204-825-9 Index number: 602-028-00-4 Reg.nr.: 01-2119475329-28	tetrachloroethylene Carc. 2, H351 Aquatic Chronic 2, H411 Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H336	50-100%
CAS: 8002-74-2 EINECS: 232-315-6	paraffin wax substance with a Community workplace exposure limit	12.5-25%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call a doctor immediately. Induce vomiting only, if affected person is fully conscious.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 2)

SECTION 5: Firefighting measures**5.1 Extinguishing media**

· Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters· Protective equipment:

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Protect from heat.

7.2 Conditions for safe storage, including any incompatibilities· Storage:· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

· Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

· Storage class:

6.1 C

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**· Additional information about design of technical facilities:

No further data; see item 7.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 3)

· Ingredients with limit values that require monitoring at the workplace:

127-18-4 tetrachloroethylene

WEL	Short-term value: 275 mg/m ³ , 40 ppm
	Long-term value: 138 mg/m ³ , 20 ppm
	Sk

8002-74-2 paraffin wax

WEL	Short-term value: 6 mg/m ³
	Long-term value: 2 mg/m ³

· DNELs**127-18-4 tetrachloroethylene**

Oral	DNEL (Langzeit-wiederholt)	1.3 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	39.4 mg/kg bw/day (ARB)
		23 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	275 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	138 mg/m ³ Air (ARB)
		34.5 mg/m ³ Air (BEV)

· PNECs**127-18-4 tetrachloroethylene**

PNEC (wässrig)	11.2 mg/l (KA)
	0.0051 mg/l (MW)
	0.051 mg/l (SW)
	364 mg/l (WAS)
PNEC (fest)	0.01 mg/kg Trockengew (BO)
	0.0903 mg/kg Trockengew (MWS)
	0.903 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Short term filter device:
Filter A/P2

· Protection of hands:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Skin protection recommendation for skin cleaning after product handling:
Kresto Classic (<http://debstoko.com>)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 4)

referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR
Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:**Tightly sealed goggles****SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:

Form:	Pasty
Colour:	Transparent
Odour:	Characteristic

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	121 °C

· Flash point: >61 °C· Ignition temperature: >300 °C· Auto-ignition temperature: Product is not selfigniting.· Explosive properties: Product does not present an explosion hazard.· Vapour pressure at 20 °C: 22 hPa· Density at 20 °C: 1.4 g/cm³· Solubility in / Miscibility with water: Not miscible or difficult to mix.· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 5)

· **Solvent content:**
 Organic solvents: 82.5 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
 - Reacts with strong acids and oxidising agents.
 - Reacts with earth alkaline metals.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
 - strong oxidizing agents
 - bases
 - Acids
- **10.6 Hazardous decomposition products:**
 - Hydrogen chloride (HCl)
 - Phosgen
 - Chlorine
 - Chlorine compounds

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal	LD50	>1,212 mg/kg (rabbit)
--------	------	-----------------------

127-18-4 tetrachloroethylene

Oral	LD50	3,005 mg/kg (rat)
Dermal	LD50	>1,000 mg/kg (rabbit)
Inhalative	LC50/4h	4,000 mg/m ³ (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 6)

SECTION 12: Ecological information**· 12.1 Toxicity**· Aquatic toxicity:**127-18-4 tetrachloroethylene**

EC50/48h	8.5 mg/l (daphnia magna)
NOELR/21d	510 mg/l (daphnia magna)
EC50/72h	3.64 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	5 mg/l (Oncorhynchus mykiss)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:· Remark:

Toxic for fish

· Additional ecological information:· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment· PBT:

Not applicable.

· vPvB:

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods**· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:· Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information**· 14.1 UN-Number**· ADR, IMDG, IATA

UN1897

· 14.2 UN proper shipping name· ADR1897 TETRACHLOROETHYLENE solution,
ENVIRONMENTALLY HAZARDOUS· IMDGTETRACHLOROETHYLENE solution, MARINE
POLLUTANT· IATA

TETRACHLOROETHYLENE solution

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 7)

· 14.3 Transport hazard class(es)**· ADR**

· Class
· Label

6.1 (T1) Toxic substances.
6.1

· IMDG

· Class
· Label

6.1 Toxic substances.
6.1

· IATA

· Class
· Label

6.1 Toxic substances.
6.1

· 14.4 Packing group

· ADR, IMDG, IATA

III

· 14.5 Environmental hazards:

· Marine pollutant:

Product contains environmentally hazardous substances:
Yes
Symbol (fish and tree)
Symbol (fish and tree)

· Special marking (ADR):

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):
· EMS Number:
· Segregation groups
· Stowage Category
· Stowage Code

Warning: Toxic substances.
60
F-A,S-A
Liquid halogenated hydrocarbons
A
SW2 Clear of living quarters.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ)

Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ)
· Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1897 TETRACHLOROETHYLENE SOLUTION, 6.1, III, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2021

Version number 8

Revision: 12.08.2021

Trade name: Solid Wax

(Contd. of page 8)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

- VOC EU 1,155.0 g/l

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
 - H351 Suspected of causing cancer.
 - H411 Toxic to aquatic life with long lasting effects.
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
- Abbreviations and acronyms:
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - SVHC: Substances of Very High Concern
 - vPvB: very Persistent and very Bioaccumulative
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - Carc. 2: Carcinogenicity – Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2