

FUGAPROOF GROUT PROTECTION

ALL TYPES OF GROUTING

water
-based



WHAT IT'S FOR

- Protects and sanitizes grouting
- Facilitates dirt removal and routine cleaning
- Prevents water and stains from being absorbed into the surface

ADVANTAGES

- Ecological product: water-based
- Ready to use and easy to apply
- Safe for use with a spray applicator
- VOC free: eco-friendly treatment
- Will not alter the colour of grouting
- Odourless
- Water-based technology: drastically reduces treatment times
- Can be applied to surfaces with residual humidity

HOW TO USE IT

No dilution required: The product is ready to use.

Instructions for use: Clean the surface using **FUGANET** detergent. When the surface is dry, spray **FUGAPROOF** directly onto the grouting and dry any excess product using a cloth. The surface can be walked on after 4 hours

COVERAGE

With 750 ml of product:

up to 850 linear metres

Coverage is indicative of one coat a may vary according to the material

Packaging

750 ml bottles with spray nozzle in boxes of 6.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

Warning

Do not wet the surface in the first 24 hours after treatment.

*Any dry residues that were not removed during application can be removed with **MANUTENZIONE PER TUTTE LE SUPERFICI** or **CLEANER PRO**, diluted 1:30.*

PROTECTORS

FIA
surface care solutions

member of





CONCRETE AND FLEXIBLE GROUT



WHAT IT'S FOR

- Protects and sanitizes grouting
- Facilitates dirt removal and routine cleaning
- Prevents water and stains from being absorbed into the surface

ADVANTAGES

- Ecological product: water-based
- Ready to use and easy to apply
- Safe for use with a spray applicator
- VOC free: eco-friendly treatment
- Will not alter the colour of grouting
- Odourless
- Water-based technology: drastically reduces treatment times
- Can be applied to surfaces with residual humidity

HOW TO USE IT

No dilution required: The product is ready to use.

Application instructions

Spray **FUGAPROOF** directly onto the clean and dry surface at a distance of roughly 10-15 cm away from the application point. Rub into the grouting with a sponge to improve penetration. Fully remove any residues within 5 minutes, either manually using a clean cloth or absorbent paper towel. Treat a small area at a time (1 m²). The floor can be walked on after 8 hours. Any remaining residues on the surface can be removed with **FILACLEANER** diluted 1:30.

COVERAGE

With one litre:
up to 600 linear metres

Coverage is indicative of one coat a may vary according to the material

Warning

Wait at least 24 hours before wetting the surface. Do not apply the product externally if rain is forecast.

Packaging

500ml bottles with spray nozzle in boxes of 12.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

COMPOSITION

Water suspension of organic resins.

LABELLING

No safety and risk labelling or instructions are required, as the product is not classified as hazardous under current regulations.
Pursuant to It.Leg.Dec. No.161/06:
Category: Binding primers (waterproofing).
EU limit value (Cat: 1/h): 30 g/l (2010).
This product contains no more than 0 g/l.

TECHNICAL FEATURES

Appearance: liquid
Colour: transparent pale yellow
Odour: spirit-based
Density: 1.010 kg/l
pH: 4.6

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.