NOPAINT STAR

GEL CLEANER FOR WALLS



NOPAINT STAR is a fast-action. effective paint stripper for walls that removes graffili from treated and untreated walls Cleans and degreases deeply. Removes smog and dust from external walls. Removes film-forming and coaling products from terracolta surfaces.



COVERAGE



"Coverage is approximate"

Packaging

1 litre: boxes of 12.

WARNINGS

Keep out of reach of children.
Do not disperse into the environment after use.

TEMPERATURES

ICMPENALURES Storage temperature: from 5° to 30° C. The product should be applied to materials with temperature between 5° and 30°C.





PORCELAIN TILES. MARBLE. GRANITE AND NATURAL STONE, AGGLOMERATES, GLAZED **CERAMIC TILES, CONCRETE, PLASTER, TERRACOTTA. OUARRY TILES**

WHAT IT'S FOR

- · Removes graffiti from treated and untreated walls: it is particularly effective on rough or porous surfaces (concrete/plaster walls, bricks, natural stone...).
- Removes WET, WETECO and PT10 protectors if they have been incorrectly applied or when thorough cleaning is required.
- · Viscous consistency: ideal for wall applications.
- · Provides in-depth cleaning and degreasing.
- · Cleans smog and dust from external walls.
- Removes film-forming and coating products from terracotta surfaces.

ADVANTAGES

- · Easy to use.
- · Ready to use: no dilution required.
- · Water-based paint remover.
- · Rapid and highly efficient.

HOW TO USE IT

No dilution required: to be used undiluted.

Application:

1. Apply the product directly on the wall with a large, flat paintbrush or using the airless method.

- 2. Leave for at least 5 minutes.
- 3. Intervene with mechanical means.

4. Rinse. For best results, use a water-jet cleaner on vertical surfaces and a single-disc cleaning machine on floors. Repeat application of the product and the consequent rinsing, if necessary (for example, on porous surfaces such as brick walls, natural stone etc.).

To remove possible residues of film-forming products such as WET, WET ECO in the event of incorrect application: simply apply the undiluted product directly onto the surface with a brush or by spraying. After 15 minutes, rub with a brush or floor scrubber and rinse well with water. Repeat the application in the event of obstinate treatments.





FILANOPAINT STAR WATER-BASED GEL CLEANER FOR WALLS





 TERRACOTTA
 QUARRY TILES
 PORCELAIN TILES
 STONE AND AGGLOMERATES
 GLAZED CERAMIC TILES
 CONCRETE
 PLASTER



WHAT IT'S FOR

- Removes graffiti from treated and untreated walls: it is particularly effective on rough or porous surfaces (cement/ plaster walls, bricks, natural stone...).
- Removes FILAWET, FILAWETECO and FILAPT10 protectors if they have been incorrectly applied or when thorough cleaning is required.
- Viscous consistency: ideal for wall applications.
- Provides in-depth cleaning and degreasing.
- Cleans smog and dust from external walls.
- It removes filming and painting products from terracotta surfaces.

ADVANTAGES

- Easy to use.
- Ready to use: no dilution required.
- Water-based paint remover.
- Rapid and highly efficient.

HOW TO USE IT

No dilution required: to be used undiluted.

Application:

- 1. Apply the product directly on the wall with a large, flat paintbrush or using the airless method.
- 2. Leave for at least 5 minutes.
- 3. Rub using a coarse cloth.
- 4. Rinse.

For best results, use a water-jet cleaner on vertical surfaces and a single-disc cleaning machine on floors

Repeat application of the product and the consequent rinsing, if required (for example, on porous surfaces such as bricks, natural stone etc.)

Packaging

1 litre cans in boxes of 12.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.

TEMPERATURES

<u>Storage temperature: from 5° to 30° C.</u> The product should be applied to materials with temperature between 5° and 30°C.

CONTAINS

Non-ionic surfactants less than 5%.

LABELLING

Warning: Danger Hazard indication: Causes serious eye damage. May cause drowsiness or dizziness. Caution recommendations: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Use only outdoors or in a wellventilated area. Wear eye protection / face protection. Immediately call a POISON CENTER / doctor. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents / container in accordance with local/ regional national/international regulation. Contains: Alcohols C12-14, ethoxylated. PROPYLENE GLYCOL, MONO METHYL ETHER, N-BUTYL ACETATE.



This information is the result of our most up-todate technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.



 FILA
 <th



FI APS87

pH 12.7



COVERAGE With one litre:

"Coverage is approximate"

5 m²