



## SATIN-EFFECT PROTECTIVE WAX

**TERRACOTTA, QUARRY TILES, UNPOLISHED STONE AND AGGLOMERATES, CONCRETE, CONCRETE TILES**



### WHAT IT'S FOR

- Ideal both for treatment and maintenance.
- Protects unpolished natural stones (limestone, slate, etc.), red stoneware, non-vitrified quarry tiles and various types of terracotta.
- Recommended for treating floors made of: slate, manufactured stone and concrete tiles.
- Highly recommended for maintenance of marble and natural stone with brushed finish.

### ADVANTAGES

- The product is self-polishing, but can also be polished to restore or increase shine.
- A 3-in-one solution: protects, maintains and gives floors an excellent finish.
- Original new satin look.
- Ideal to create prestigious floors: enhances the beauty of the surface.
- Easy to apply and maximum coverage.
- Does not degenerate with maintenance.



### COVERAGE

With one litre:

Terracotta 30 m<sup>2</sup>

Stone 30/40 m<sup>2</sup>

"Coverage shown is for guidance purposes only and refers to single coats"

### Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

### WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost. Store at room temperature.

### TEMPERATURES

Storage temperature: from 5° to 30° C.  
This product must be applied to surfaces with temperature between 10°C and 30°C.

### HOW TO USE IT

**Dilution:** either undiluted or diluted according to requirements. Using fleece or other applicator, apply an even coat of the product on the clean and dry floor. After one hour, apply a second coat at right angles to the first. The floor can be walked on after roughly half an hour. For improved sheen, buff the surface with a floor polisher or woollen cloth.

#### For maintenance:

**Restoring sheen (every 2-3 months):** after cleaning the surface with a diluted solution of **CLEANER PRO** (1:200), apply **SATIN** diluting 500 ml of product in 5 litres of water. For greater shine, wait till floor is dry (after about 1 hour) and buff with a wool cloth or floor polisher.

**To restore the finish (once a year):** apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour). apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour).

#### Caution:

*Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).*