Safety Data Sheet KERAQUICK XL FIBRELITE

Safety Data Sheet dated: 04/02/2020 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: KERAQUICK XL FIBRELITE

Trade code: 9001258

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Cement based powder adhesive

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD www.mapei.co.uk (office hour 8:30-17:30)

Responsable: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)1684 299 886

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960

SECTION 2: Hazards identification





2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1B May cause an allergic skin reaction. STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Dange

Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

8 to do. Continue rinsing.

P312 Call a POISON CENTER if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains:

Portland cement, Cr(VI) < 2 ppm

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 1 of 10

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: KERAQUICK XL FIBRELITE

Hazardous components within the meaning of the CLP regulation and related classification:

| Quantity | Name | Ident. Numb. | Classification | Registration Number |
|-----------------------|--|--------------------------------|---|---------------------|
| ≥25 - <50 % | Portland cement, Cr(VI) < 2 ppm | | Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Dam. 1, H318; STOT SE 3, H335 | |
| ≥25 - <50 % | free crystalline silica (Ø >10 μ) | CAS:14808-60-7 EC:238-878-4 | | |
| ≥0.0015 - <0.005 % | free crystalline silica (Ø <10 μ) | CAS:14808-60-7 EC:238-878-4 | STOT RE 2, H373 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Eve irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 2 of 10

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

| Component | OEL Type | Country | Ceiling | Long Term mg/m3 | Long Term ppm | Short Term mg/m3 | Short Term ppm | Behaviour | Note |
|---------------------------------|-------------|-----------------|---------|--------------------|------------------|------------------------|-------------------|-----------|--|
| Portland cement, Cr(VI) < 2 ppm | < National | FINLAND | | 1 | | | | | FINLAND, respirabel fraktion |
| | NDS | POLAND | | 6 | | | | | frakcja wdychalna |
| | NDS | POLAND | | 2 | | | | | frakcja respirabilna |
| | SUVA | SWITZERLAN D | | 5 | | | | | A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory |

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 3 of 10

5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10 mg/m3 TWA (containing <1% of free Silica, total dust)

inhalable dust

respirable dust

A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory symptoms; asthma 5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10

mg/m3 TWA (containing <1% of free Silica, total

dust)

5 mg/m3 TWA (containing <1% of free Silica,

respirable dust);10

| DFG National | GERMANY SPAIN | 15 4,000 | |
|------------------|---|-------------|--------|
| National | FINLAND | 5,000 | |
| | FINLAND | 1,000 | |
| | PORTUGAL | 10 | |
| | BELGIUM | 10 | |
| NDS | POLAND | 6,000 | |
| | | | |
| NDS | POLAND | 2,000 10 | |
| | HUNGARY MALAYSIA | | |
| a OEL | MALATSIA | 10,000 | |
| National | Ι ΔΤ\/ΙΔ | 6,000 | |
| National | | 10,000 | |
| National | | 4,000 | |
| | | 10.000 | 40.000 |
| | CROATIA | 10,000 | 10,000 |
| DFG | GERMANY C | 15 | |
| ACGIH | AUSTRALIA | 1,000 | |
| Malaysi a OEL | MALAYSIA | 10 | |
| National | UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND | 10 | 30,000 |

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 4 of

IRELAND

| | | | | | dust) |
|--|----------|---|--------|--------|---|
| | National | I UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND | 10 | 12,000 | |
| | National | I UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND | 4,000 | | |
| | National | I ROMANIA | 10 | | |
| | National | I CROATIA | 10,000 | | |
| | National | I CROATIA | 4,000 | 10 | |
| free crystalline silica (Ø >10 μ) | NDS | POLAND | 0,300 | | frakcja respirabilna |
| | National | I DENMARK | 0,3 | | DENMARK, inhalable aerosol inhalable aerosol |
| | National | I DENMARK | 0,100 | | DENMARK, respirable aerosol respirable aerosol |
| | SUVA | GERMANY | 0,150 | | 50 μg/m³ (Partikel Durchmesser < 12 μm) - TRGS 906 |
| | National | l SWITZERLAN D | 0,15 | | Α |
| | ACGIH | NNN | 0,025 | | (R), A2 - Pulm fibrosis, lung cancer |
| | National | I NORWAY | 0,300 | | K 7 |
| free crystalline silica (Ø <10 μ) | National | I SWEDEN | 0,100 | | SWEDEN, respirable aerosol |
| | National | I NORWAY | 0,100 | | K 7 |
| | NDS | POLAND | 2,000 | | frakcja wdychalna |
| | NDS | POLAND | 0,300 | | frakcja respirabilna |
| | National | I DENMARK | 0,3 | 0,600 | DENMARK, inhalable aerosol inhalable aerosol |
| | National | I DENMARK | 0,100 | 0,200 | DENMARK, respirable aerosol respirable aerosol |
| | EU | NNN | 0,1 | | A2 (R) - Pulm fibrosis, lung cancer |

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 5 of 10

(R), A2 -Pulm fibrosis, lung cancer

National AUSTRIA 0,150 A

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min. Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour: Powder white/grey

Odour: Cement like
Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: N.A. Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.
Vapour pressure: N.A.
Relative density: N.A.
Apparent density: 1.5
Solubility in water: <5 g/l

Partition coefficient (n-octanol/water): N.A. - This product is a mixture

Auto-ignition temperature: N.A. - No explosive or spontaneous ignition in contact with air at room temperature

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: == - No components with explosive properties

Oxidizing properties: N.A. - No component with oxidizing properties

Solid/gas flammability: N.A.

9.2. Other information

No additional information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 6 of 10

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

free crystalline silica (Ø

a) acute toxicity

LD50 Oral > 2000 mg/kg

>10 µ)

LD50 Skin > 2000 mg/kg

free crystalline silica (Ø

a) acute toxicity

LD50 Oral Rat = 500 mg/kg

<10 µ)

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- k) Toxicological kinetics, metabolism and distribution information
- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

No Data Available

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 7 of 10

national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Product

Do not dispose of waste into sewers.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to an authorized waste disposal service.

Contaminated packaging:

Empty remaining content.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number

N.A.

14.2. UN proper shipping name

N.A

14.3. Transport hazard class(es)

N.A

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): N.A. g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) 2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

German Water Hazard Class

N.A.

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 8 of 10

Restrictions related to the substances contained: 69

SVHC Substances:

No Data Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

| Code | Description | | | | |
|----------------|---|--|--|--|--|
| H315 | Causes skin irritation. | | | | |
| H317 | May cause an allergic skin reaction. | | | | |
| H318 | Causes serious eye damage. | | | | |
| H335 | May cause respiratory irritation. | | | | |
| H373 | May cause damage to organs through prolonged or repeated exposure . | | | | |
| Cada | | Description | | | |
| Code | Hazard class and hazard category | Description | | | |
| 3.2/2 | Skin Irrit. 2 | Skin irritation, Category 2 | | | |
| | 5 , | • | | | |
| 3.2/2 | Skin Irrit. 2 | Skin irritation, Category 2 | | | |
| 3.2/2 3.3/1 | Skin Irrit. 2 Eye Dam. 1 | Skin irritation, Category 2 Serious eye damage, Category 1 | | | |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| Classification according to Regulat (EC) Nr. 1272/2008 | tion Classification procedure |
|--|-------------------------------|
| 3.2/2 | Calculation method |
| 3.3/1 | Calculation method |
| 3.4.2/1B | Calculation method |
| 3.8/3 | Calculation method |

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

Page n. 9 of 10 07/02/2020 Production Name KERAQUICK XL FIBRELITE Date

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 5. FIRE-FIGHTING MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 13. DISPOSAL CONSIDERATIONS
- 15. REGULATORY INFORMATION

Date 07/02/2020 Production Name KERAQUICK XL FIBRELITE Page n. 10 of 10